

TG-LS-048 / Product Parameter Summary

Flexible Light Strip



Listed parameters

Supply voltage	HV/LV
Dimensions	Not specified
Power	8 W (measurement basis unspecified)
Luminous flux	650 lm (measurement basis unspecified)
Color rendering	Ra≥70/80
Cutting interval	2.5cm/cut Or 5cm/cut Or 100cm/cut
Color wording	3000K/4000K/6500K/red/blue/green/pink/gold/lemon/ice blue

Product overview

LED strip lights

Reviewed catalog statements for this product. Independent test evidence has not been verified for this summary. This is not a complete technical datasheet or installation guide.

DEVELOPMENT PREVIEW

Specification notes

- Power and luminous flux bases are unspecified; do not interpret as per metre or rank efficiency/brightness.
- HV/LV is literal; numeric voltage, AC/DC, direct mains and required accessories are not established.
- Dimensions and bend characteristics are unspecified; unitless model tokens establish no geometry.
- Cutting alternatives are literal and unassigned to configurations; no LED density is established.
- Mixed color wording is literal, not numeric CCT options, channels, controls, compatibility or variants.
- Ra≥70/80 is literal, not a bound, range, assigned alternatives or verified test conditions.
- IP, suitability, uniformity, certification, lifetime, warranty and availability are not established.